

SAFETY DATA SHEET

2500 Hard-Hat® Clear

1. Identification of the preparation and of the company

Product name and/or code : Andrews Coatings Ltd. Carver Building, Littles Lane
Product use :
Manufacturer : Wolverhampton, West Midlands, WV1 1JY
 Telephone Number: 01902 429190, Fax Number: 01902 426574
Emergency phone: : Email: sales@andrewscoatings.co.uk

2. Composition/information on ingredients

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC.

Chemical name*	CAS no.	%	EC nr.	Classification
United Kingdom (UK)				
Dimethyl ether	115-10-6	25 - 50	204-065-8	F+; R12
Xylene (mixture of isomeres)	1330-20-7	25 - 50	215-535-7	R10 Xn; R20/21 Xi; R38
1-Methoxy-2-propanol	107-98-2	2.5 - 5	203-539-1	R10
2,2,4-Trimethyl-1,3-pentanediol-di-isobutyrate	6846-50-0	1 - 2.5	229-934-9	N; R51/53
See section 16 for the full text of the R-phrases declared above				

Occupational exposure limits, if available, are listed in section 8.

3. Hazards identification

The preparation is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : F+; R12
 Xn; R20/21
 Xi; R38
Physical/chemical hazards : Extremely flammable.
Human health hazards : Harmful by inhalation and in contact with skin.
 Irritating to skin.
Additional warning phrases : Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

4. First aid measures

First aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.
Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use solvents or thinners.
Eye contact : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.
Ingestion : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting.

5. Fire-fighting measures

Extinguishing media : Recommended: alcohol-resistant foam, CO₂, powders, water spray.
 Not to be used : water jet.
Recommendations : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Bursting aerosol containers may be propelled from a fire at high speed. Cool closed containers exposed to fire with water. Do not release runoff from fire to sewers or waterways.

5. Fire-fighting measures

Hazardous combustion products : Decomposition products may include the following materials:
carbon oxides

6. Accidental release measures

Personal precautions : Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.

Spill : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Preferably clean with a detergent. Avoid using solvents. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

Note: see section 8 for personal protective equipment and section 13 for waste disposal.

7. Handling and storage

Handling : Vapors may travel along ground and flashback along vapor trail. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits.

Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see section 8).

Comply with the health and safety at work laws.

Storage : Store in accordance with local regulations. Observe label precautions. Do not store above the following temperature: 35°C (95°F). Store in a cool, well-ventilated area away from incompatible materials and ignition sources.

Keep away from: oxidizing agents, strong alkalis, strong acids.

No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage..

8. Exposure controls/personal protection

Engineering measures : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.

<u>Ingredient name</u>	<u>Occupational exposure limits</u>
United Kingdom (UK)	
Dimethyl ether	EH40-WEL (United Kingdom (UK), 1/2005). STEL: 958 mg/m ³ , 0 times per shift, 15 minute(s). Form: All forms STEL: 500 ppm, 0 times per shift, 15 minute(s). Form: All forms TWA: 766 mg/m ³ , 0 times per shift, 8 hour(s). Form: All forms TWA: 400 ppm, 0 times per shift, 8 hour(s). Form: All forms
Xylene (mixture of isomeres)	EH40-WEL (United Kingdom (UK), 1/2005). Skin STEL: 441 mg/m ³ 15 minute(s). Form: All forms STEL: 100 ppm 15 minute(s). Form: All forms TWA: 220 mg/m ³ 8 hour(s). Form: All forms TWA: 50 ppm 8 hour(s). Form: All forms
1-Methoxy-2-propanol	EH40-WEL (United Kingdom (UK), 1/2005). Skin STEL: 560 mg/m ³ , 0 times per shift, 15 minute(s). STEL: 150 ppm, 0 times per shift, 15 minute(s). TWA: 375 mg/m ³ , 0 times per shift, 8 hour(s). TWA: 100 ppm, 0 times per shift, 8 hour(s).

8. Exposure controls/personal protection

Exposure controls

- Occupational exposure controls** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Respiratory protection** : Recommended: organic vapor (Type AX) and particulate filter (EN 140) .
- Hand protection** : >8 hours (breakthrough time): Rubber gloves, nitrile rubber (EN 374-1) .
- Eye protection** : Recommended:safety glasses with side-shields
- Skin protection** : Additional body garments should be used to avoid exposed skin surfaces (e.g. sleevelets, apron, disposable suit etc.), based on the task being performed. Appropriate techniques should be used to remove potentially contaminated clothing.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Environmental exposure controls

Do not allow to enter drains or watercourses.

9. Physical and chemical properties

- Physical state** : Liquid. (Aerosol.)
- Odor** : Hydrocarbon.
- Color** : Colorless.
- Flash point** : - 40 °C
- Boiling point** : -25°C (-13°F)
- Explosion limits** : Lower: 3% Upper: 18%
- Vapor pressure** : 420 kPa (propellant)
- Vapor density** : > 1
- Volatility %** : 86% (w/w).
- VOC content w/w** : 662 (g/l).
- Relative density** : 0.78 (Water = 1)

10. Stability and reactivity

Stable under recommended storage and handling conditions (see section 7).

Hazardous decomposition products: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

11. Toxicological information

There is no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 2 and 15 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
-------------------------	--------	---------	------	----------

11. Toxicological information

Dimethyl ether	LC50 Inhalation	Rat	308000 mg/m ³	1 hours
	Gas.			
Xylene (mixture of isomeres)	LC50 Inhalation	Mouse	386 ppm	0,5 hours
	Gas.			
	LD50 Dermal	Rabbit	>1700 mg/kg	-
1-Methoxy-2-propanol	LD50 Oral	Rat	4300 mg/kg	-
	LC50 Inhalation	Rat	5000 ppm	4 hours
	Vapor			
2,2,4-Trimethyl-1,3-pentanediol-di-isobutyrate	LD50 Dermal	Rabbit	13000 mg/kg	-
	LD50	Rat	3720 mg/kg	-
	Intraperitoneal			
	LD50 Dermal	Rabbit	13 g/kg	-
	LD50 Intravenous	Rat	4200 mg/kg	-
	LD50 Oral	Rat	6600 mg/kg	-
	LD50	Rat	7800 mg/kg	-
	Subcutaneous			
	LDLo Oral	Rat	3739 mg/kg	-
	LC50 Inhalation	Rat	55000 mg/m ³	4 hours
2,2,4-Trimethyl-1,3-pentanediol-di-isobutyrate	Vapor			
	LCLo Inhalation	Rat	7000 ppm	6 hours
	Vapor			
	LD50 Dermal	Guinea pig	>18900 mg/kg	-
2,2,4-Trimethyl-1,3-pentanediol-di-isobutyrate	LD50 Oral	Mouse	>6400 mg/kg	-
	LD50 Oral	Rat	>3200 mg/kg	-
	LC50 Inhalation	Rat	>5,3 mg/L	6 hours
	Vapor			

12. Ecological information

There is no data available on the preparation itself.
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

Aquatic ecotoxicity

Product/ingredient name	Test	Result	Species	Exposure
Xylene (mixture of isomeres)	Mortality	Acute LC50 13,4 mg/L	Fish - Fathead minnow (pimephales promelas)	96 hours
	Mortality	Acute LC50 12 mg/L	Fish - Bluegill sunfish (lepomis macrochirus)	96 hours
	Mortality	Acute LC50 8,2 mg/L	Fish - Rainbow trout (oncorhynchus mykiss)	96 hours
1-Methoxy-2-propanol	-	Acute LC50 20800 mg/l	Fish - Fathead minnow (pimephales promelas)	96 hours
2,2,4-Trimethyl-1,3-pentanediol-di-isobutyrate	NOEC	Acute EC50 >1,55 mg/L	Daphnia	48 hours
	NOEC	Acute LC50 >1,55 mg/L	Fish	96 hours

Ecological information

Biodegradability

Product/ingredient name	Test	Result	Dose	Inoculum
Xylene (mixture of isomeres)	-	90 % - Readily - 5 days	-	-
1-Methoxy-2-propanol	-	>90 % - Readily - 5 days	1,95 gO ₂ /g ThOD	-

Conclusion/Summary : Our database contains no additional remark on the biodegradation of this product

Product/ingredient name

Xylene (mixture of isomeres)
1-Methoxy-2-propanol

Aquatic half-life

-
< 28 day(s)

Photolysis

-
-

Biodegradability

Readily
Readily

Bioaccumulative potential

Product/ingredient name

Dimethyl ether
Xylene (mixture of isomeres)
1-Methoxy-2-propanol

LogP_{ow}

0.1
3.2
<1

BCF

-
-
-

Potential

low
high
low

13. Disposal considerations

Do not allow to enter drains or watercourses.
Dispose of according to all federal, state and local applicable regulations.


European waste catalogue (EWC) : The European Waste Catalogue classification of this product, when disposed of as waste, is: 20 01 27* paint, inks, adhesives and resins containing dangerous substances. If this product is mixed with other wastes, this code may no longer apply. If mixed with other wastes, the appropriate code should be assigned. For further information, contact your local waste authority.

Hazardous waste : Yes.

14. Transport information

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

International transport regulations

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
ADR/RID Class	1950	AEROSOLS, flammable Limited quantity	2	-		Hazard identification number 23 Limited quantity LQ2 CEFIC Tremcard 20G53 Remarks Limited Quantity - ADR/IMDG 3.4.6
IMDG Class	1950	AEROSOLS, flammable Limited quantity	2.1	-		Emergency schedules (EmS) F-D, S-U Remarks Limited Quantity - ADR/IMDG 3.4.6
IATA Class	1950	AEROSOLS, flammable		-		Quantity limitation - Passenger aircraft - Limited quantity 30 kg Quantity limitation - Passenger aircraft 75 kg Quantity limitation - Cargo aircraft 150 kg Packaging instruction 203 (<6 bar @ 20°C)

PG* : Packing group

15. Regulatory information

EU regulations : The product is classified and labelled for supply in accordance with the Directive 1999/45/EC as follows:

Hazard symbol(s) :



Extremely flammable, Harmful

Risk phrases :

R12- Extremely flammable.
R20/21- Harmful by inhalation and in contact with skin.
R38- Irritating to skin.

Safety phrases :

S2- Keep out of the reach of children.
S23- Do not breathe vapor or spray.
S36/37- Wear suitable protective clothing and gloves.
S51- Use only in well-ventilated areas.
S56- Dispose of this material and its container at hazardous or special waste collection point.

Contains :

Xylene (mixture of isomeres)

Other EU regulations

Additional warning phrases : Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

15. Regulatory information

Tactile warning of danger : Yes, applicable.

CN code : 3208 10 90

National regulations

16. Other information

CEPE Classification : 1

Full text of R-phrases : R12- Extremely flammable.

referred to in sections 2 and R10- Flammable.

3 - United Kingdom (UK) R20/21- Harmful by inhalation and in contact with skin.

R38- Irritating to skin.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

The information in this Safety Data Sheet is required pursuant to EU Directive 91/155/EEC and its amendments.

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties. ©Copyright by Rust-Oleum Netherlands B.V. / Martin Mathys B.V.



Version	1	v.3.4.	<i>Page: 6/6</i>
Date of issue	30-5-2007.		<i>Printed 9-7-2007.</i>

