



SAFETY DATA SHEET

8399 Masonry Sealer

1. Identification of the preparation and of the company

Product name and/or code : 8399 Masonry Sealer
Product use : Andrews Coatings Ltd. Carver Building, Littles Lane
Manufacturer : Wolverhampton, West Midlands, WV1 1JY
Emergency phone: : Telephone Number: 01902 429190, Fax Number: 01902 426574
 Email: sales@andrewscoatings.co.uk

2. Composition/information on ingredients

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC.

Chemical name*	CAS no.	%	EC nr.	Classification
United Kingdom (UK) Naphtha (petroleum), hydrotreated heavy	64742-48-9	25 - 50	265-150-3	R10 Xn; R65 R66
Tolyfluanide	731-27-1	0 - 1	211-986-9	T; R23 Xn; R48/20 Xi; R36/37/38 R43 N; R50/53
See section 16 for the full text of the R-phrases declared above				

Occupational exposure limits, if available, are listed in section 8.

3. Hazards identification

The preparation is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : R10
 R43, R66
 R52/53
Physical/chemical hazards : Flammable.
Human health hazards : May cause sensitization by skin contact. Repeated exposure may cause skin dryness or cracking.
Environmental hazards : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

4. First aid measures

First aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.
Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use solvents or thinners.
Eye contact : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.
Ingestion : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting.

5. Fire-fighting measures

Extinguishing media : Recommended: alcohol-resistant foam, CO₂, powders, water spray.
 Not to be used : water jet.
Recommendations : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to sewers or waterways.

5. Fire-fighting measures

Hazardous combustion products : Decomposition products may include the following materials:
carbon oxides
halogenated compounds
metal oxide/oxides

6. Accidental release measures

Personal precautions : Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.

Spill : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Preferably clean with a detergent. Avoid using solvents. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

Note: see section 8 for personal protective equipment and section 13 for waste disposal.

7. Handling and storage

Handling : Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.

Put on appropriate personal protective equipment (see section 8).

Comply with the health and safety at work laws.

Storage : Store in accordance with local regulations. Observe label precautions. Do not store above the following temperature: 35°C (95°F). Store in a cool, well-ventilated area away from incompatible materials and ignition sources.

Keep away from: oxidizing agents, strong alkalis, strong acids.

No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Do not empty into drains.

8. Exposure controls/personal protection

Engineering measures : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.

<u>Ingredient name</u>	<u>Occupational exposure limits</u>
United Kingdom (UK) Naphtha (petroleum), hydrotreated heavy	EH40-WEL (United Kingdom (UK), 6/2005). Notes: as Turpentine STEL: 850 mg/m ³ 15 minute(s). STEL: 150 ppm 15 minute(s). EH40-WEL (United Kingdom (UK), 6/2005). Notes: as Turpentine TWA: 566 mg/m ³ 8 hour(s). TWA: 100 ppm 8 hour(s).

Exposure controls

Occupational exposure controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

8. Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Respiratory protection** : Recommended: organic vapor (Type A) and particulate filter (EN 140).
- Hand protection** : >8 hours (breakthrough time): gloves, nitrile rubber or neoprene (EN 374-1) .
- Eye protection** : Recommended: safety glasses with side-shields (EN 166) .
- Skin protection** : Recommended: overall (EN 1149-1) .
Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other protection** : Additional body garments should be used to avoid exposed skin surfaces (e.g. sleevelets, apron, disposable suit etc.), based on the task being performed.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Environmental exposure controls

Do not allow to enter drains or watercourses.

9. Physical and chemical properties

- Physical state** : Liquid.
- Odor** : Hydrocarbon.
- Color** : White.
- Flash point** : Closed cup: 40°C (104°F) [Setaflash.]
- Boiling point** : >160°C (>320°F)
- Explosion limits** : Lower: 0.6%
Upper: 8%
- Vapor pressure** : 0.7 kPa (5.25 mm Hg)
- Vapor density** : >1 [Air = 1]
- Evaporation rate (butyl acetate = 1)** : 0.2 (Butyl acetate. = 1)
- Volatility %** : 58.7% (v/v), 34.3% (w/w)
- VOC content w/w** : 526 (g/l).
- Solubility** : Partially soluble in the following materials: acetone.
Very slightly soluble in the following materials: methanol.
Insoluble in the following materials: cold water, hot water, diethyl ether and n-octanol.
- Relative density** : 1.32
- Viscosity** : Dynamic: 1800 mPa·s (1800 cP)

10. Stability and reactivity

Stable under recommended storage and handling conditions (see section 7).

Hazardous decomposition products: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

11. Toxicological information

There is no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 2 and 15 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage.

Contains tolylfluanid. May produce an allergic reaction.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
-------------------------	--------	---------	------	----------

11. Toxicological information

Naphtha (petroleum), hydrotreated heavy	LD50 Dermal	Rabbit	>3000 mg/kg	-
	LD50 Oral	Rat	>15000 mg/kg	-
	LC50 Inhalation Vapor	Rat	>5,5 mg/L	4 hours
Tolyfluanide	LD50 Dermal	Rat	500 mg/kg	-
	LD50 Oral	Rat	1 g/kg	-
	LD50 Oral	Rat	500 mg/kg	-
	LD50 Subcutaneous	Rat	500 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	300 mg/m ³	4 hours

12. Ecological information

There is no data available on the preparation itself.
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See sections 2 and 15 for details.

Aquatic ecotoxicity

Product/ingredient name	Test	Result	Species	Exposure
Naphtha (petroleum), hydrotreated heavy	-	Acute EC50 >1000 mg/L	Daphnia	4 hours
	-	Acute IC50 >1000 mg/L	Algae	4 hours
	-	Acute LC50 >1000 mg/L	Fish	4 hours
Tolyfluanide	-	Acute EC50 0,69 mg/L	Daphnia	48 hours
	-	Acute LC50 0,055 mg/L	Fish - Golden orfe (leuciscus idus)	96 hours
	-	Acute LC50 0,045 mg/L	Fish - Rainbow trout (oncorhynchus mykiss)	96 hours
	-	Acute LC50 >1 mg/l	Algae - Scenedesmus subs.	72 hours

Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Naphtha (petroleum), hydrotreated heavy	< 28 day(s)	-	Readily
Tolyfluanide	1.5 day(s); pH: 7; 20°C	-	-

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Naphtha (petroleum), hydrotreated heavy	4.9 to 6.5	-	high
Tolyfluanide	3.3	74	high

AOX : The product contains organically bound halogens and can contribute to the AOX value in waste water.

13. Disposal considerations

Do not allow to enter drains or watercourses.
Dispose of according to all federal, state and local applicable regulations.

European waste catalogue (EWC) : The European Waste Catalogue classification of this product, when disposed of as waste, is: 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances. If this product is mixed with other wastes, this code may no longer apply. If mixed with other wastes, the appropriate code should be assigned. For further information, contact your local waste authority.

Hazardous waste : Yes.


14. Transport information

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

International transport regulations


Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
ADR/RID Class	--	-	-	-		Remarks Exempted according to 2.2.3.1.5 (Viscous substance exemption)

14. Transport information

IMDG Class	--	-	-	-		Emergency schedules (EmS) F-E, S-E Remarks Exempted according to 2.3.2.5 (Viscous substance exemption)
IATA Class	1263	Paint. (Naphtha (petroleum), hydrotreated heavy)	3	III		Passenger and Cargo Aircraft Quantity limitation: 60 L Packaging instructions: 309 Cargo Aircraft Only Quantity limitation: 220 L Packaging instructions: 310 Limited Quantities - Passenger Aircraft Quantity limitation: 10 L Packaging instructions: Y309 Special provisions: A72

PG* : Packing group

15. Regulatory information

EU regulations	: The product is classified and labelled for supply in accordance with the Directive 1999/45/EC as follows:
Hazard symbol(s)	: 
	Irritant
Risk phrases	: R10- Flammable. R43- May cause sensitization by skin contact. R66- Repeated exposure may cause skin dryness or cracking. R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Safety phrases	: S24- Avoid contact with skin. S37- Wear suitable gloves. S51- Use only in well-ventilated areas. S61- Avoid release to the environment. Refer to special instructions/safety data sheet.
Contains	: Tolyfluanide
Europe inventory	: Europe inventory: Not determined.
Other EU regulations	
CN code	: 3208 10 90
National regulations	

16. Other information

CEPE Classification	: 1
Full text of R-phrases referred to in sections 2 and 3 - United Kingdom (UK)	: R10- Flammable. R23- Toxic by inhalation. R48/20- Harmful: danger of serious damage to health by prolonged exposure through inhalation. R65- Harmful: may cause lung damage if swallowed. R36/37/38- Irritating to eyes, respiratory system and skin. R43- May cause sensitization by skin contact. R66- Repeated exposure may cause skin dryness or cracking. R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

The information in this Safety Data Sheet is required pursuant to EU Directive 91/155/EEC and its amendments.

[Notice to reader](#)

16. Other information

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties. ©Copyright by Rust-Oleum Netherlands B.V. / Martin Mathys B.V.



Version	1.01	v.3.4.	<i>Page: 6/6</i>
Date of issue	10-4-2007.		<i>Printed 9-7-2007.</i>



Rustoleum Aerosols, Carver Building, Littles Lane, Wolverhampton WV1 1JY
Tel: 01902 712286 Email: sales@rustoleumaerosols.co.uk
Fax: 01902 426574 Web: www.rustoleumaerosols.co.uk