



# SAFETY DATA SHEET

9170 / 9180 High Performance Epoxy Primers (Base)

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Product name and/or code** : 9170 / 9180 High Performance Epoxy Primers (Base)

**Manufacturer** : Rust-Oleum Netherlands BV, PO. Box 138, NL-4700 AC Roosendaal, The Netherlands  
NV Martin Mathys, Kolenbergstraat 23, B-3545 Zelem, Belgium

**Emergency phone number** : Andrews Coatings Ltd. Carver Building, Littles Lane  
Wolverhampton, West Midlands, WV1 1JY  
Telephone Number: 01902 429190, Fax Number: 01902 426574  
Email: sales@andrewscoatings.co.uk

**e-Mail address of person responsible for this SDS** : Andrews Coatings Ltd. Carver Building, Littles Lane  
Wolverhampton, West Midlands, WV1 1JY  
Telephone Number: 01902 429190, Fax Number: 01902 426574  
Email: sales@andrewscoatings.co.uk

**Distributor** : Andrews Coatings Ltd. Carver Building, Littles Lane  
Wolverhampton, West Midlands, WV1 1JY  
Telephone Number: 01902 429190, Fax Number: 01902 426574  
Email: sales@andrewscoatings.co.uk

**Product use** : Andrews Coatings Ltd. Carver Building, Littles Lane  
Wolverhampton, West Midlands, WV1 1JY  
Telephone Number: 01902 429190, Fax Number: 01902 426574  
Email: sales@andrewscoatings.co.uk

## 2. HAZARDS IDENTIFICATION

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

**Classification** : R10  
Xn; R20/21  
Xi; R38  
R52/53

**Physical/chemical hazards** : Flammable.

**Human health hazards** : Harmful by inhalation and in contact with skin. Irritating to skin.

**Environmental hazards** : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC.

Chemical name	CAS #	%	EU no.	Classification
xylene (mixture of isomers)	1330-20-7	10 - 25	215-535-7	R10 Xn; R20/21 Xi; R38 [1] [2]
1-methoxy-2-propanol	107-98-2	5 - 10	203-539-1	R10 [2]
trizinc bis(orthophosphate)	7779-90-0	1 - 2.5	231-944-3	N; R50/53 [1]
See section 16 for the full text of the R-phrases declared above				

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in section 8.

## 4. FIRST AID MEASURES

### First aid measures

**General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

**Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.

**Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use solvents or thinners.

**Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.

**Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting.

## 5. FIRE-FIGHTING MEASURES

- Extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.  
Not to be used : water jet.
- Recommendations** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
phosphorus oxides  
metal oxide/oxides

## 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.
- Spill** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Preferably clean with a detergent. Avoid using solvents. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

**Note:** see section 8 for personal protective equipment and section 13 for waste disposal.

## 7. HANDLING AND STORAGE

- Handling** : Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits.
- In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.
- Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used.
- Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding.
- Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.
- Put on appropriate personal protective equipment (see section 8).
- Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one.
- Comply with the health and safety at work laws.
- Storage** : Store in accordance with local regulations. Observe label precautions. Do not store above the following temperature: 35°C (95°F). Store in a cool, well-ventilated area away from incompatible materials and ignition sources.
- Keep away from: oxidizing agents, strong alkalis, strong acids.  
No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.  
Do not empty into drains.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Engineering measures** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.

### Ingredient name

Xylene (mixture of isomers)

1-methoxy-2-propanol

### Occupational exposure limits

**EH40-WEL (United Kingdom (UK), 9/2006). Skin**

WEL 15 min limit: 441 mg/m<sup>3</sup> 15 minute(s).

WEL 8 hrs limit: 220 mg/m<sup>3</sup> 8 hour(s).

**EH40-WEL (United Kingdom (UK), 9/2006). Skin**

WEL 15 min limit: 560 mg/m<sup>3</sup> 15 minute(s).

WEL 8 hrs limit: 375 mg/m<sup>3</sup> 8 hour(s).

### Exposure controls/personal protection

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Occupational exposure controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: organic vapor (Type A) and particulate filter (EN 140) .
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. >8 hours (breakthrough time): gloves, polyvinyl alcohol (PVA) or nitrile rubber (EN 374) .  
*Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.*
- Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Recommended: safety glasses with side-shields (EN 166) .
- Skin protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: overall .
- Other protection** : When spraying and sanding, suitable respiratory protection must be used. Air-fed protective respiratory equipment must be worn by the spray operator, even when good ventilation is provided. In other operations, if local exhaust ventilation and good general extraction are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn. (See Personal Protection.) In confined spaces, use compressed-air or fresh-air respiratory equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state** : Liquid.
- Odor** : Solvent-like.
- Color** : Brownish-red or grey.
- Flash point** : Closed cup: 25°C (77°F) [Setaflash.]
- Boiling point** : >140°C (>284°F)
- Explosion limits** : Lower: 2%  
Upper: 12%
- Vapor pressure** : 0.6 kPa (4.5 mm Hg)
- Vapor density** : >1 [Air = 1]
- Evaporation rate (BuAc=1)** : 0.7 (Butyl acetate. = 1)
- Volatility %** : 46 to 49% (v/v), 27 to 32% (w/w)
- Viscosity** : Dynamic: 1500 to 3000 mPa·s (1500 to 3000 cP)
- Relative density (kg/L)** : 1.37 to 1.43

## 10. STABILITY AND REACTIVITY

Stable under recommended storage and handling conditions (see section 7).

Hazardous decomposition products: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

## 11. TOXICOLOGICAL INFORMATION

There is no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 3 and 15 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption

**11. TOXICOLOGICAL INFORMATION**

through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage.

**Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
xylene (mixture of isomers)	LD50 Intraperitoneal	Rat	2459 mg/kg	-
	LD50 Oral	Rat	4300 mg/kg	-
	LD50 Subcutaneous	Rat	1700 mg/kg	-
	LC50 Inhalation Gas.	Rat	5000 ppm	4 hours
	LC50 Inhalation Vapor	Rat	5000 ppm	4 hours
1-methoxy-2-propanol	LD50 Intraperitoneal	Rat	3720 mg/kg	-
	LD50 Oral	Rat	6600 mg/kg	-
	LD50 Subcutaneous	Rat	7800 mg/kg	-
	LDLo Oral	Rat	3739 mg/kg	-
	LC50 Inhalation Vapor	Rat	55000 mg/m <sup>3</sup>	4 hours
	LC50 Inhalation Gas.	Rat	10000 ppm	5 hours
	LCLo Inhalation Vapor	Rat	7000 ppm	6 hours
trizinc bis(orthophosphate)	LD50 Intraperitoneal	Rat	551 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
	TDLo Intratracheal	Rat	250 mg/kg	-

**12. ECOLOGICAL INFORMATION**

There is no data available on the preparation itself.  
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See sections 2 and 15 for details.

**Aquatic ecotoxicity**

Ingredient name	Test	Result	Species	Exposure
xylene (mixture of isomers)	-	Acute LC50 13500 to 19200 ug/L Fresh water	Fish - Rainbow trout,donaldson trout - Oncorhynchus mykiss - 0.9 g	96 hours
	-	Acute LC50 13400 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - 31 days - 18.4 mm - 0.077 g	96 hours
1-methoxy-2-propanol	-	Acute LC50 13500 to 16100 ug/L Fresh water	Fish - Bluegill - Lepomis macrochirus - 1.1 g	96 hours
	-	Acute EC50 >1000 mg/l	Algae - Selenastrum capricomutum	7 days
	-	Acute LC50 20800 mg/l	Fish - Fathead minnow	96 hours
trizinc bis(orthophosphate)	-	Acute LC50 23300 mg/l	Daphnia	96 hours
	-	Acute EC50 <1.7 mg/L	Daphnia - Daphnia Magma	48 hours
	-	Acute IC50 <0.3 mg/L	Algae - Desmodesmus subspicatus	72 hours
	-	Acute LC50 90 ug/L Fresh water	Fish - Rainbow trout,donaldson trout - Oncorhynchus mykiss - 180 days - 1.5 g	96 hours

**Ecological information****Biodegradability**

Ingredient name	Test	Result	Dose	Inoculum
xylene (mixture of isomers)	-	90 % - Readily - 5 days	-	-
1-methoxy-2-propanol	OECD 301E	96 % - Readily - 28 days	-	-
	-	>90 % - Readily - 5 days	1.95 gO <sub>2</sub> /g ThOD	-
	OECD 301C	88 to 92 % - Readily - 28 days	-	-

**Conclusion/Remark** : This product has not been tested for biodegradation.

Ingredient name	Aquatic half-life	Photolysis	Biodegradability
Xylene (mixture of isomers)	-	-	Readily
1-methoxy-2-propanol	Fresh Water 25,2 days	-	Readily

**Bioaccumulative potential**

Ingredient name	LogP <sub>ow</sub>	BCF	Potential
Xylene (mixture of isomers)	3.2	-	high
1-methoxy-2-propanol	-0.49	<100	low

**13. DISPOSAL CONSIDERATIONS**

Do not allow to enter drains or watercourses.  
Dispose of according to all federal, state and local applicable regulations.


**European waste catalogue (EWC)** : The European Waste Catalogue classification of this product, when disposed of as waste, is: 08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances. If this product is mixed with other wastes, this code may no longer apply. If mixed with other wastes, the appropriate code should be assigned. For further information, contact your local waste authority.

**Hazardous waste** : Yes.

**14. TRANSPORT INFORMATION**

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**International transport regulations**

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
<b>ADR/RID Class</b>	- -	-	-	-		<b>Remarks</b> Exempted according to 2.2.3.1.5 (Viscous substance exemption)
<b>IMDG Class</b>	1263	Paint.	3	III		<b>Emergency schedules (EmS)</b> F-E, S-E  <b>Remarks</b> Exempted according to 2.3.2.5 (Viscous substance exemption)
<b>IATA Class</b>	1263	Paint.	3	III		<b>Passenger and Cargo Aircraft</b> Quantity limitation: 60 L Packaging instructions: 309 <b>Cargo Aircraft Only</b> Quantity limitation: 220 L Packaging instructions: 310 <b>Limited Quantities - Passenger Aircraft</b> Quantity limitation: 10 L Packaging instructions: Y 309

PG\* : Packing group

The "viscosity exemption" provisions do not apply to air transport.

**15. REGULATORY INFORMATION****EU regulations**

: The product is classified and labelled for supply in accordance with the Directive 1999/45/EC as follows:

**Hazard symbol or symbols**

Harmful

**Risk phrases**

: R10- Flammable.  
R20/21- Harmful by inhalation and in contact with skin.  
R38- Irritating to skin.  
R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Safety phrases**

: S23- Do not breathe vapor or spray.  
S36/37- Wear suitable protective clothing and gloves.  
S43- In case of fire, use DRY chemicals, CO<sub>2</sub>, alcohol resistant foam or water spray.  
S51- Use only in well-ventilated areas.  
S61- Avoid release to the environment. Refer to special instructions/safety data sheet.

**Contains**

: Xylene (mixture of isomeres)

**VOC for Ready-for-Use Mixture**

: IIA/j. Two-pack reactive performance coatings for specific end use such as floors. EU limit values: 550g/l (2007) 500g/l (2010.)  
This product contains a maximum of 493 g/l VOC.

**Europe inventory**

: **Europe inventory:** Not determined.

**Other EU regulations****CN code**

: 3208 10 90

**Industrial use**

: The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

**16. OTHER INFORMATION****CEPE Classification**

: 1

**16. OTHER INFORMATION**

**Full text of R-phrases referred to in sections 2 and 3 - United Kingdom (UK)** :

- R10- Flammable.
- R20/21- Harmful by inhalation and in contact with skin.
- R38- Irritating to skin.
- R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

The information in this Safety Data Sheet is required pursuant to EU Directive 91/155/EEC and its amendments.

✔ Indicates information that has changed from previously issued version.

Notice to reader

*The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties. ©Copyright by Rust-Oleum Netherlands B.V. / Martin Mathys B.V.*



<b>Version</b>	0.05	v.4.0.	<i>Page: 6/6</i>
<b>Date of issue</b>	2009-01-09.		<i>Printed 2009-01-09.</i>



Rustoleum Aerosols, Carver Building, Little Lane, Wolverhampton WV1 1JY  
 Tel: 01902 712286 Email: [sales@rustoleumaerosols.co.uk](mailto:sales@rustoleumaerosols.co.uk)  
 Fax: 01902 426574 Web: [www.rustoleumaerosols.co.uk](http://www.rustoleumaerosols.co.uk)