

## PRODUCT DATA

## 25 - GREEN SUPER PAINT STRIPPER

**Andrews Coatings Ltd**  
Carver Building  
Littles Lane  
Wolverhampton  
West Midlands  
WV1 1JY

**Tel. 01902 429190**

info@rustoleumdirect.co.uk  
www.rustoleumdirect.co.uk

### DESCRIPTION

RUST-OLEUM® Green Super Paint Stripper is a highly effective paint dissolving/lifting material without methylene chloride for exterior use.

### RECOMMENDED USES

RUST-OLEUM® Green Super Paint Stripper can be used for a quick removal of layers of old paint and glue.

RUST-OLEUM® Green Super Paint Stripper is developed to remove all types of oil- and alkyd-based paints, emulsion paints, varnish and most two-component materials from metal, mineral and wooden surfaces.

RUST-OLEUM® Green Super Paint Stripper does not contain methylene chloride, NMP, acids, alkali's, biocides and conservation additives. It will not affect metal, mineral or wooden substrates.

### TECHNICAL DATA

Appearance: Clear, thixotropic layer

Composition: Special blend of solvents and paraffin wax

VOC-content: 900 g/l

### Coverage

Theoretical: 250 - 500 g/m<sup>2</sup> ≈ 2 - 4 m<sup>2</sup>/l.

Practical: Practical usage depends on many factors such as type and amount of contaminants, shape of the substrate and material losses during application.

### DIRECTION FOR USE

Remove loose coatings as much as possible by scraping.

To release possible pressure open the can carefully.

Apply RUST-OLEUM® Green Super Paint Stripper thickly in an even layer with a brush (disposable brush, flat or round). Do not use synthetic brushes.

Allow to stand for 10 to 15 minutes, and remove the old layer with a filling knife or paint scraper.

Thick layers of some (two-component) products may need an additional treatment.

After use, clean the surface with a cleaner (f.e. ND 14), high pressure (steam) cleaning, fresh water and allow to dry completely before applying a coating.

### APPLICATION CONDITIONS

Temperature of air, substrate and material between 5 and 35°C and relative humidity below 85%.

### REMARKS

RUST-OLEUM® Green Super Paint Stripper may affect plastic materials alike e.g. PVC, polystyrene. In case of doubt, try on a small test patch beforehand.

### SAFETY

Do not use in the immediate vicinity of flames, hot surfaces or welding works.

No smoking. Use only outdoors.

Consult Safety Data Sheet and Safety Information printed on the can.

### SHELLIFE / STORAGE CONDITIONS

1 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.