

569/580

QUICK DRYING METAL PRIMER

Single pack quick drying metal primer for bare and lightly rusted metal

The one-day maintenance system.

Technical reference

	Solvent based
Coverage:	12.8 m ² /l. at 35 µm dry
Dry to touch:	1 hrs
Dry to recoat:	2 hrs
Colours:	Red brown, grey + tintable
Pack sizes:	1L, 5L, 20L
Substrates:	New, blasted or slightly rusted steel
Recoatable with:	1060/1080, 7500, 9100



Metal

Metal Primer 569

Topcoat



- Recoatable after just 2 hours.
- Durable maintenance in a single day.
- Universal metal primer for alkyd (7500) and epoxy (9100)
- Brush, roller or spray application



1060/1080

HEAVY-DUTY METAL PRIMER

The long-life metal protection system for coastal or industrial areas.

Higher film build per coat

Standard Metal Primer 35 µm	RUST-OLEUM® 1060 60 µm
--------------------------------	---------------------------



- High build (60 µm in a single layer)
- High content of rust-inhibiting pigments
- Lasting flexibility
- Durable corrosion protection (Class C3-C4)
- For new, blasted or lightly rusted steel
- Effective over adherent mill scale
- Application by brush, roller or spray



Maximum durability under severely corrosive conditions.

Technical reference

	Solvent based
Coverage:	9 m ² /l. at 60 µm dry
Dry to touch:	4 hrs
Dry to recoat:	24 hrs
Colours:	Orange, grey + tintable
Pack sizes:	1L, 5L, 20L (1080 only)
Substrates:	New or blasted steel
Recoatable with:	7500 ALKYTHANE® For more technical information see page 64-67

