

9600

RUST-O-THANE®

Flexible high-gloss polyurethane topcoat



9600: Resistant against strong chemicals

A very durable, colourfast and chemical resistant system

- For coated floors or walls
- Very easy to clean
- Resistant against strong chemicals
- Suitable for high humidity and moist conditions
- High abrasion resistance, low wear
- Flexible and impact resistant
- For heavy industrial and marine exposures
- Drying can be accelerated with Accelerator 9996

Technical reference

| | |
|-------------------------|--|
| | Solvent based |
| Coverage: | 13.2 m ² /l. at 40 µm dry |
| Dry to touch: | 6 hrs (use 9996 accelerator for shorter dry times) |
| Dry to recoat: | 16 hrs (use 9996 accelerator for shorter dry times) |
| Colours: | Tintable |
| Pack sizes: | 5L |
| Substrates: | Concrete or metal treated with RUST-OLEUM® epoxy systems |
| Recoatable with: | Not applicable |

Standard colours:



Note: Minor differences between above printed and supplied colours is possible. ColourShop®

9200

RUST-O-THANE®

Water based satin gloss polyurethane



Polyurethane technology that offers outstanding colour and gloss retention

Technical reference

| | |
|-------------------------|--|
| | Water based |
| Coverage: | 9,2 m ² /l. at 40 µm dry |
| Dry to touch: | 2 hrs |
| Dry to recoat: | 24 hrs |
| Colours: | See colour card + tintable |
| Pack sizes: | 2,5L, 5L |
| Substrates: | Concrete and metal prepared with RUST-OLEUM® epoxy systems |
| Recoatable with: | Not applicable |

- Long lasting satin finish
- Stable colours
- Very durable
- Excellent wear resistance
- Very low VOC

